

Product Number 840

Issuing Date No data available

Revision Date 03-11-2015

Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Acetone

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Multi-purpose solvent

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Sunnyside Corporation
Supplier Address 225 Carpenter Avenue
Wheeling
IL
60090
US
Supplier Phone Number Phone:8003238611
Fax:8475419043
Supplier Email sscontact@sunnysidecorp.com
Emergency telephone number Chem Trec 8004249300

2. HAZARDS IDENTIFICATION

Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

GHS Label elements, including precautionary statements



Emergency Overview

Signal word		Danger	
Hazard Statements			
Causes serious eye irritation			
May cause drowsiness or dizziness			
Highly flammable liquid and vapor			
			
Appearance	Clear	Physical State	Liquid
		Odor	Pungent

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Wear protective gloves/protective clothing/eye protection/face protection
Keep cool

Precautionary Statements - Response**Skin**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful if inhaled
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Acetone	67-64-1	60 - 100	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES**First aid measures****General Advice**

Show this safety data sheet to the doctor in attendance.

Eye Contact

If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.

Skin Contact

In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed**Most Important Symptoms and Effects**

Burning sensation. Drowsiness. Dizziness.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable Extinguishing Media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Uniform Fire Code

Flammable Liquid: I-B
Irritant: Liquid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Other Information

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment

A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Soak up with inert absorbent material. Dike far ahead of liquid spill for later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers.

Incompatible Products

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL = 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 1800 mg/m ³ (vacated) TWA: 750 ppm (vacated) STEL: 1000 ppm (vacated) STEL: 2400 mg/m ³	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Tight sealing safety goggles.

Skin and Body Protection

Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Liquid	Odor	Pungent
Appearance	Clear	Odor Threshold	No information available
Color	Colorless		
<u>Property</u>	<u>Values</u>	<u>Remarks/ Method</u>	
pH	N/A	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	56 °C / 133 °F	None known	
Flash Point	-18 C / 0 F	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	N/A	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	2.5% @ 77 °F		
Vapor pressure	213 mmHg @ 75 °F	None known	
Vapor density	No data available	None known	
Specific Gravity	data available	None known	
Water Solubility	Soluble in water	None known	
Solubility in other solvents	data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	869 °F	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing Properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	Exempt
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Caustics, amines, alkanolamines, ammonia, strong oxidizing agents and chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Specific test data for the substance or mixture is not available. May cause drowsiness and dizziness based on components. May cause irritation of respiratory tract.

Eye Contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. May cause redness, itching, and pain. May cause temporary eye irritation.

Skin Contact

Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	-	-	= 50100 mg/m ³ (Rat) 8 h

Information on toxicological effects

Symptoms

May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure



Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	Contains no ingredient listed as a carcinogen.
Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic Toxicity	No known effect based on information supplied.
Target Organ Effects	Eyes. Central Nervous System (CNS). Respiratory system. Skin.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist)

100.20 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Chemical Name	Log Pow
Acetone 67-64-1	-0.24

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001 U002

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1				U002

California Hazardous Waste Codes 212

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone 67-64-1	Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Description CONSUMER COMMODITY, ORM-D
Emergency Response Guide Number 127

TDG

UN-No. UN1090
Proper Shipping Name ACETONE
Hazard Class 3
Packing Group II
Description UN1090, ACETONE, 3, II

MEX

UN-No. UN1090
Proper Shipping Name ACETONE
Hazard Class 3
Packing Group II
Description UN1090 ACETONE, 3, II

ICAO

UN-No. UN1090
Proper Shipping Name ACETONE
Hazard Class 3
Packing Group II
Description UN1090, ACETONE, 3, II

IATA

UN-No. UN1090
Proper Shipping Name ACETONE
Hazard Class 3



Packing Group	II
Description	UN1090, ACETONE, 3, II

IMDG/IMO

UN-No.	UN1090
Proper Shipping Name	ACETONE
Hazard Class	3
Packing Group	II
EmS No.	F-E, S-D
Description	UN1090, ACETONE, 3, II, FP -18C

RID

UN-No.	UN1090
Proper Shipping Name	ACETONE
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1090 ACETONE, 3, II

ADR

UN-No.	UN1090
Proper Shipping Name	ACETONE
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1090 ACETONE, 3, II

ADN

UN-No.	UN1090
Proper Shipping Name	ACETONE
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1090 ACETONE, 3, II
Hazard Labels	3
Limited Quantity	1 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No



CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone 67-64-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Acetone 67-64-1	X	X	X	X	

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Acetone 67-64-1 (60 - 100)		Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m ³ Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada**WHMIS Hazard Class**

B2 - Flammable liquid

D2B - Toxic materials

**16. OTHER INFORMATION**

NFPA	Health Hazards 2	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 2	Flammability 3	Physical Hazard 0	Personal Protection X

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Revision Date	15-Sep-2014
Revision Note	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet